



AMU
MAHAN
ENERGY

White Spirit BA

| Property | Test method | Unit | Result |
|------------------|-------------|------|--------|
| Density@15.56° © | ASTM D-1298 | - | 0.795 |
| Flash Point | ASTM D-93 | ° © | 49-52 |
| Color | ASTM D-86 | | 0.25 |
| IBP | ASTM D-86 | ° © | 160 |
| 5% | ASTM D-86 | ° © | 179 |
| 15% | ASTM D-86 | ° © | 210 |
| 20% | ASTM D-86 | ° © | 226 |
| 30% | ASTM D-86 | ° © | 171 |
| 40% | ASTM D-86 | ° © | 174 |
| 50% | ASTM D-86 | ° © | 177 |
| 60% | ASTM D-86 | ° © | 183 |
| 70% | ASTM D-86 | ° © | 190 |

| | | | |
|------------|------------------|------------|------------|
| 80% | ASTM D-86 | ° © | 206 |
| 90% | ASTM D-86 | ° © | 208 |
| 95% | ASTM D-86 | ° © | 258 |
| FBP | | ° © | 263 |



Acceptance

Consignee/Buyer

Website: www.amumahanenergy.com
Email: info@amumahanenergy.com

Mobile: +98 9108583235
Office at Unit 4, Fl 11, Nahid Tower,
Madar Sq. Mirdama Blvd, Tehran, Iran.